

		metric   imperial	JET FIVE
<b>Axes Configuration</b>			
<b>Process Technology</b>			Milling
<b>Working Area</b>	<i>X-Axis Stroke</i>	mm   in.	from 3.000 to 12.000   from 118.1 to 472.4
	<i>Y-Axis Stroke</i>	mm   in.	from 1.500 to 2.500   from 59.0 to 98.4
	<i>Z-Axis Stroke</i>	mm   in.	from 600 to 3.000   from 23.6 to 118.1
	<i>X/Y/Z Axis Rapid Feed</i>	m/min   ipm	40 / 70 (Linear Motors)   1,574.8 / 2,755.9 (Linear Motors)
<b>Pallet</b>	<i>Option 1</i>	mm   in.	3.000 x 2.000   118.1 x 78.7
	<i>Option 2<sup>2</sup></i>	mm   in.	6.000 x 2.000   236.2 x 78.7
<b>Rotary Table (B-Axis)</b>	<i>Max. Rotation Speed</i>	min-1	–
<b>5th Axis (A-Axis)</b>	<i>Type</i>		Bi-Rotary Head
	<i>Tilting Angle</i>	Degrees	±110 (A) ±360 (C)
<b>Spindle Unit</b>	<i>Tool - Taper</i>		HSK / ISO
	<i>Speed Range</i>	min-1	from 4.000 up to 30.000
<b>Tool Magazine</b>	Capacity ( up to)1	No.	199 (450)
<b>Available Configurations</b>			