

		metric imperial	TANK.G 2000		
Axes Configuration			4-Axes	5-Axes	5 Axes-Multitasking
Process Technology			–	Milling	Milling, Turning, Grinding
Working Area	X-Axis Stroke	mm in.	2.000 78.7	2.000 78.7	2.000 78.7
	Y-Axis Stroke	mm in.	2.000 78.7	1.700 66.9	1.700 66.9
	Z-Axis Stroke	mm in.	2.000 78.7	2.000 78.7	2.000 78.7
	X/Y/Z Axis Rapid Feed	m/min ipm	45 1,771.7	45 1,771.7	45 1,771.7
Pallet	Option 1	mm in.	1.000 x 1.000 39.3 x 39.3	1.000 x 1.000 39.3 x 39.3	Ø 1.000 Ø 39.3
	Option 2 ²	mm in.	1.250 x 1.250 49.2 x 49.2	1.250 x 1.250 49.2 x 49.2	Ø 1.250 Ø 49.2
Rotary Table (B-Axis)	Max. Rotation Speed	min-1	20	20	200
5th Axis (A-Axis)	Type		–	Tilting Head	Tilting Head
	Tilting Angle	Degrees	–	175 (+80/-95)	175 (+80/-95)
Spindle Unit	Tool-Taper		HSK / ISO / CAPTO		
	Speed Range	min-1	from 6.000 up to 30.000		
Tool-Magazine	Capacity (up to)1	No.	80 (999)	80 (999)	80 (999)
Available Configurations			Single-Pallet/Twin-Pallet / Multipallet / FMS		