

		metric imperial	TANK.G 3000		
Axes Configuration			4-Axes	5-Axes	5 Axes-Multitasking
Process Technology			Milling	Milling	-
Working Area	X-Axis Stroke	mm in.	3.000 118.1	3.000 118.1	-
	Y-Axis Stroke	mm in.	2.500 98.4	2.500 98.4	-
	Z-Axis Stroke	mm in.	2.500 98.4	2.500 98.4	-
	X/Y/Z Axis Rapid Feed	m/min ipm	40 – 40 – 32 1,574.8 – 1,574.8 – 1,259.8	40 – 40 – 32 1,574.8 – 1,574.8 – 1,259.8	-
Pallet	Option 1	mm in.	1.250 x 1.250 49.2 x 49.2	1.250 x 1.250 49.2 x 49.2	-
	Option 2 ²	mm in.	1.250 x 1.600 49.2 x 63.0	1.250 x 1.600 49.2 x 63.0	-
Rotary Table (B-Axis)	Max. Rotation Speed	min-1	8 / 15	8 / 15	-
5th Axis (A-Axis)	Type		-	Tilting Head	-
	Tilting Angle	Degrees	-	175 (+80/-95)	-
Spindle Unit	Tool-Taper		HSK / ISO / CAPTO		-
	Speed Range	min-1	from 6.000 up to 30.000		-
Tool-Magazine	Capacity (up to)1	No.	80 (999)	80 (999)	-
Available Configurations			Single-Pallet/ Twin-Pallet / Multipallet / FMS		